PROCO

The Expansion Joint and Check Valve People

ProFlex™ Rubber Check Valves Series 700

PROCO SERIES 700

The PROCO Series 700 *ProFlex*™ Rubber Check Valves are a cost effective way to control back pressures from sewage treatment plants, outfalls and tidal operations. They are a fully passive flow device requiring neither maintenance nor any outside sources of power or manual assistance to operate.

The PROCO Series 700 *ProFlex*™ Check valves are offered as direct replacements for ineffective and maintenance ridden flap type check valves, commonly known to seize, rust and bind in unwanted positions. Unlike flap type valves, the *ProFlex*™ rubber check valves will handle large obstructions without jamming or having swing gates binding open. Specify the PROCO Series 700 *ProFlex*™ rubber check valves to provide backflow protection from (1) Sewage slurries, (2) Outfalls to ocean fronts from heavy rainfall activity, (3) Prevention from land erosion due to back flow conditions, (4) Protection from saltwater to fresh water ponds and catch basins and numerous other water based applications. Our history in the manufacture of rubber piping products dates back to 1930. When an engineered solution is needed to solve a piping or backflow problem, call PROCO.

The Proco Series 700 ProFlex™ Rubber Check Valves are available in the following styles:

- **Style 710: Flanged**: Designed to bolt directly to existing flanges or new installations, flanges are drilled to ANSI 125/150# standard. Other drilling standards are also available upon request. The style 710 can be installed in either vertical or horizontal applications.

- **Style 710TT: Flanged Blending System Valves**: The Patented Torsionally twisted valve is designed to bolt directly on existing or any new installations. This valve is supplied to ensure proper mixing in potable water reservoirs and tanks. The torsional design ensures quick and accurate blending which provides a properly blended volume of potable water.

  The Hydraulic Blending Analysis provided by Proco (based on CFD and engineered scale modeling) supplies the contractor/end user with strategic location points for each valve. All valves will be ANSI/NSF-61 certified.

- **Style 711/731 Flanged/Slip-on Slope Bottom Check Valve**s: Designed for installation on pre-existing or new pipe lines such as manholes, outfalls, vaults, where the outfall invert of the pipe is close to the floor of the manhole or outfall. Can be engineered into the pipe layout with little concern for outfall clearance due to its "low slope" design.

Table 1: Available Materials • Temperatures

For Specific Elastomer Recommendations, See: **PROCO™ "Chemical To Elastomer Guide"**

PROCO Material Codes	Cover [3] Elastomer	Tube Elastomer	Maximum Operating Temp. °F (°C)	
BB	Chlorobutyl	Chlorobutyl	250°	(121°)
EE	EPDM	EPDM	250°	(121°)
NH	Neoprene	CSM	212°	(100°)
NN	Neoprene	Neoprene	225°	(107°)
NN-NSF61 [2]	Neoprene	Neoprene	225°	(107°)
PP	Nitrile	Nitrile	212°	(100°)
NR	Neoprene	Natural Rubber	180°	(82°)

Notes: ProFlex™ is a trademark of PROCO Products, Inc.
All products are reinforced with polyester tire cord.
1. Styles with Neoprene covers meet all requirements of U.S.C.G.
2. NN-NSF/61 UL Classified Water Quality
3. Other materials available. Please contact Proco Products

- **Style 720: Flanged In-line**: Designed to fit directly inside of an existing pipe. Supplied with a flat face rubber flange which allows installation between existing pipe flanges eliminating the requirement for a valve body. Flanges are drilled to ANSI 125/150# standard. Other drilling standards are also available upon request.

- **Style 730: Sleeve Type**: Designed to easily slip over an existing pipe, and is affixed with heavy-duty stainless steel clamps. Can be installed in either a vertical or horizontal application.

- **Style 730M: Molded Type**: Molded Type : A economical engineered valve, available in smaller pipe diameter ranging from 3/4" -6" nominal sch 40 pipe size.
  Designed to prevent odors and low back pressures from seeping back up the stream channel. Supplied with stainless steel gear clamps.

- **Style 730CBD: Coarse Bubble Diffusers**: Designed to provide excellent coarse bubble diffusion in settling ponds, tanks, reservoirs, Supplied with a stainless steel Hex nipple, PVC adapter and variable orifices, makes this the valve of choice.

- **Style 740: Slip In-Inline**: Designed to slip directly inside of an existing pipe. Supplied with a stainless steel expandable clamp to secure it in place.

- **Style 750: Jacketed**: Designed with a full metal enclosure which allows easy installation in existing piping systems. Utilizes the Style 710 as the check valve.

- **Style 770/780: Wafer Style**: Designed with a metal or plastic orifice plate and a rubber disk , this valve is an ideal valve to provide high back pressure capability on clean water applications.

- **Style 790: Low Headloss In-Line**: Designed as an all one piece constructed valve, the Style 790 is one of lowest headloss valves on the market. A passive flow device ensuring no delamination.

ELASTOMERS: All of the PROCO Series 700 *ProFlex*™ Rubber Check Valves are available in a various selection of elastomers including ANSI/NSF-61 certified product under UL Certification #MH47689. The PROCO Series 700 *ProFlex*™ Rubber Check Valves will not freeze or deform and function solely on the inlet and back pressures which will be present in each application.

Each valve is carefully constructed using the finest of engineered materials and some of the most experienced rubber technicians in the industry. All check valves are engineered in precise detail to ensure proper operation and will provide years of unhindered operation and trouble free service.

Benefits of the PROCO Series 700 ProFlex™ Rubber Check Valves:

- **All rubber construction resists abrasive slurries**
- **Barnacle resistant Neoprene is standard construction, with ANSI/NSF-61 certified valves also available**
- **Very quiet operation with no water hammer**
- **Its unique design prevents backflow**
- **Negligible maintenance and energy costs**
- **Will not warp or freeze**
- **Quick interchange with any flap type check valve**
- **Available in sizes 1"– 96"**
- **Available with special I.D to suit concrete pipe**

Proco Style 710

ProFlex™ Flanged Rubber Check Valves



Proco Style 710TT

ProFlex™ ANSI/NSF-61 Flanged Blending System Valves

Covered by U.S. Patent No. 11,396,951

Proco Style 711

ProFlex™ Flanged Slope Bottom Check Valves

Covered by US Patent Number 11,221,081

Proco Style 720

ProFlex™ In-line Flanged Rubber Check Valves

Proco Style 730

ProFlex™ Slip-on Rubber Check Valves

Proco Style 730M

ProFlex™ Low Pressure Molded Rubber Check Valves

Proco Style 730CBD

ProFlex™ Coarse Bubble Diffusers

Proco Style 731

ProFlex™ Slip-on Slope Bottom Check Valves

Covered by US Patent Number 11,221,081

Proco Style 740

ProFlex™ Slip-in Style In-line Rubber Check Valves

Proco Style 750

ProFlex™ Jacketed In-line Flanged Rubber Check Valves



Proco Style 770/780

ProFlex™ Wafer Style In-line Flanged Rubber Check Valves

Proco Style 790

ProFlex™ Low Headloss In-line Rubber Check Valves

(800) 344-3246
sales@procoproducts.com

PROCO STYLE 740

ProFlex™ Slip-in Style In-line Rubber Check Valves

The *ProFlex*™ 740 In-line Rubber Duckbill Check Valve is designed to fit directly inside of an existing pipe, and is supplied with a stainless steel internal expandable clamp to secure it in place.

For higher pressure/vacuum requirements, the ***ProFlex*™ 740** In-line Rubber Duckbill Check Valve can also be manufactured using a unique Internal Vacuum Supports (IVS) design which is homogeneous to the inner reinforced layers of the valve allowing full flow with no obstructions and yet providing excellent anti-inversion features.

Style 740											
Diameter		Standard Valve Dimensions						Max. Working Pressure		Approx. Weight	
		Cuff Width		Length		Duckbill Height					
in.	mm	in.	mm	in.	mm	in.	mm	PSI	bar	lbs	kgs
2	50	1.5	38	7.2	184	2.0	50	125	8.6	2.9	1.3
3	75	3.0	76	11.3	286	2.8	70	125	8.6	3.5	1.6
4	100	3.0	76	11.5	292	3.6	92	100	6.9	4.4	2.0
6	150	4.0	102	14.6	371	5.6	142	75	5.2	8.4	3.8
8	200	4.0	102	18.3	464	7.5	190	75	5.2	10.8	4.9
10	250	4.0	102	20.4	517	9.4	240	50	3.4	16.5	7.5
12	300	6.0	152	26.0	661	11.0	280	50	3.4	34.0	15.4
14	350	6.0	152	26.7	679	12.4	315	50	3.4	44.1	20.0
16	400	6.0	152	27.5	699	14.6	372	50	3.4	52.9	24.0
18	450	6.0	152	32.2	819	17.0	432	25	1.7	68.3	31.0
20	500	8.0	203	34.1	865	19.0	482	25	1.7	101.4	46.0
24	600	8.0	203	37.8	960	22.0	560	25	1.7	149.9	68.0
28	700	8.0	203	43.2	1098	26.5	672	25	1.7	205.0	93.0
30	750	10.0	254	51.3	1304	28.4	722	25	1.7	396.8	180.0
36	900	10.0	254	60.7	1541	34.6	879	25	1.7	330.7	150.0
40	1000	10.0	254	62.8	1594	38.7	983	25	1.7	448.3	203.3
42	1050	12.0	305	66.1	1679	40.4	1026	25	1.7	507.1	230.0
48	1200	12.0	305	73.3	1863	46.7	1186	25	1.7	648.2	294.0
54	1350	12.0	305	77.8	1976	52.7	1338	25	1.7	720.9	327.0
60	1500	12.0	305	83.7	2125	59.2	1504	25	1.7	859.8	390.0
64	1600	12.0	305	84.4	2145	63.2	1606	25	1.7	949.5	430.7
66	1650	12.0	305	85.6	2175	65.2	1656	25	1.7	994.3	451.0
72	1800	12.0	305	97.2	2468	71.5	1816	25	1.7	1128.8	512.0

Notes: Higher back pressures can be provided by using internal vacuum supports and/or engineered Hi-Tensile reinforcement, contact PROCO.

1. *Dimensions are approximate and may change due to pipe dimension changes, inlet, back pressures and flow rates.*
2. *Larger sizes available upon request.*
3. *Weights are approximate..*

Available Elastomers
Neoprene (Barnacle and Algae Resistant), ANSI/NSF-61, EPDM, Nitrile, Natural Rubber, CSM and Chlorobutyl.



Detail of the ***ProFlex***™ Slip-in In-line Rubber Check Valve; Style 740



(800) 344-3246
sales@procoproducts.com

Frequently Asked Questions

ProFlex™ Check Valves

1. Does the *ProFlex*™ rubber check valve have to be installed in a certain position?
Yes; it should be installed in a vertical position with the bill being the vertical. In zero clearance situations the valve can be rotated up to 30-35 Deg to gain bottom clearance if required.

2. In which degree can the *ProFlex*™ rubber check valve be installed?
Because the valve is not reliant on any hinges, gates, or weights the *ProFlex*™ rubber check valve can be installed in any angle from vertical to horizontal.

3. What is "Back Pressure"?
When the *ProFlex*™ rubber check valve is submerged in a liquid it is subjected to external pressure. It is critical that the maximum depth that the valve will be submerged is specified as this will be considered the maximum back pressure that the valve will be subjected to.

4. What is the cracking pressure to allow the valve to open?
It typically takes 1" to 2" of head pressure over back pressure to crack open all 700 series valve(s). For the Series 790 it will take approximately 33-50% of pipe diameter to flush the valve completely. Contact Proco for further assistance.

5. What back pressures can the *ProFlex*™ rubber check valve withstand?
Back pressures are in direct relation to the size of the valve, on the smaller diameters it is acceptable to specify up to 200 psi of back pressure and on larger diameters a back pressure limitation would be approximately 12 psi. Each *ProFlex*™ rubber check valve is manufactured to the exact line pressure, back pressure and flow rates which we require from you for manufacture. Proco can even supply valves up to 650 psi utilizing internal back pressure supports.

6. What are the most common installations?
The *ProFlex*™ 710 flanged rubber check valve is bolted directly to a head wall replacing an existing flap gate, the *ProFlex*™ 730 sleeved type rubber check valves are clamped directly to a fabricated flanged nipple or clamped directly to an existing pipe.

7. Can I use the *ProFlex*™ rubber check valve on potable water applications?
The *ProFlex*™ rubber check valves are available with an ANSI/NSF-61 certified elastomer. Due to the large demand for clean water and potable applications, this will eliminate the concerns commonly affiliated with contaminants or leaching of elastomers in potable water systems.

8. Can the *ProFlex*™ rubber check valve be installed on an "out of round" pipe?
Yes, please have the approximate dimensions from 4 different angles to provide proper sizing.

9. Can river currents and ocean waves damage the valves?
In most cases river currents and ocean waves will not damage the *ProFlex*™ rubber check valves, but if currents or waves in question are of an abnormal nature, it is suggested that side walls or rock pilings are utilized.

10. Can the *ProFlex*™ rubber check valve be used as a pressure relief valve?
The *ProFlex*™ rubber check valves have been designed to offer superior service as a backflow preventer and can also be considered as a pressure relief valve. Often used on reservoirs to prevent hydraulic lifting or floating of tanks.

11. Can PROCO make a special design to suit my requirements?
In most instances the *ProFlex*™ rubber check valve can be fabricated to suit different applications. Contact PROCO for your requirements.

12. What types of elastomer are available?
The *ProFlex*™ rubber check valves can be manufactured and supplied to withstand almost any type of media. Most commonly supplied is a barnacle and algae resistant Neoprene. Other common elastomers are EPDM, Nitrile, Natural Rubber, and elastomers to meet ANSI/NSF-61 and ANSI/NSF-372 specifications.

13. What types of materials are available for the backing rings and banding clamps?
ProFlex™ rubber check valves are supplied with 316 stainless steel backing rings and 304 stainless steel clamps as a standard. Other materials are available upon request.

14. Can the *ProFlex*™ 710 be supplied with special flanges or drilling?
Yes, the standard drilling pattern is ANSI 125/150# drilling, other drilling standards such as: ANSI 250/300#, BS-10, DIN NP-10 and DIN NP-16, JIS-5k and JIS-10K are available upon special request.

15. Can I install a *ProFlex*™ rubber check valve near a residential area?
Yes, one of the unique features of the *ProFlex*™ rubber check valve is the design of the bill section. While the bill will open and allow passage of fluid when head pressure is present, the bill will close and not allow children or animals to crawl inside when there is no head pressure.
Since the *ProFlex*™ rubber check valve is manufactured entirely of rubber compounds there is no chance of loud banging which is commonly heard from flap type valves.

16. Can I use a *ProFlex*™ rubber check valve in winter conditions?
Yes, as in any installation the *ProFlex*™ rubber check valve will not be hindered by winter or sub-zero installations. If the valve is installed in a running water application the valve will continue to operate satisfactorily, due to the elastomers unique chemical makeup. If unusual circumstances occur the *ProFlex*™ rubber check valve will freeze without any damage and will return to operation upon thaw.

17. Will the *ProFlex*™ rubber check valve operate if buried in sand or sediment?
In normal conditions the discharge flow will create a small flow pattern which will then be followed by the flow velocity of the media. This velocity will flush the rest of the sediment away from the valve opening. This has been found to be unique only to the straight bill design as supplied by Proco.


The specified Inlet Pressure opens the *ProFlex*™ Rubber Check Valve allowing flow.

18. What is the maximum temperature that the *ProFlex*™ rubber check valve can handle?
Temperature can range from – 65 Deg to +400 Deg depending on the specified elastomer.

19. What is the life expectancy of the *ProFlex*™ Rubber check valves?
All of the *ProFlex*™ valves are manufactured with the highest grade of elastomers, which commonly are known to supply 35-50 years of service life.


The specified Back Pressure forces the *ProFlex*™ Rubber Check Valve to close preventing backflow.

(800) 344-3246
sales@procoproducts.com

PROCO PRODUCTS, INC.

2431 North Wigwam Dr. (95205)
P.O. Box 590 • Stockton, CA
95201-0590 • USA

Toll-Free Phone: (800) 344-3246 NATIONWIDE AND CANADA

Facsimile: (209) 943-0242

(209) 943-6088 INTERNATIONAL

email: sales@procoproducts.com

website: http://www.procoproducts.com

American Water Works Association

Water Environment Federation® Preserving & Enhancing the Global Water Environment MEMBER

COOLING TECHNOLOGY INSTITUTE CTI EST. 1950 MEMBER ©

FLUIDSEALING ASSOCIATION

NAHAD CHARTER Listed Member SAFETY • QUALITY • RELIABILITY

UL CERTIFIED HEALTH EFFECTS US-CA MH47689

ANSI American National Standards Institute MEMBER

REPRESENTED BY:

Revised 12/23